

Compact conventional 2-zone control panel CCG-02ZMINI



Reference: CCG-02ZMINI
Product code: 21101031
EAN code: 8429898029405



Main characteristics



- 2-zone control panel for use with conventional detectors and push buttons.
- Up to 32 devices (total detectors and push buttons) per zone.
- 2 supervised general siren outputs, timer adjustable from 0 to 7 minutes.
- 1 immediate alarm output via a dry contact NO/NC.
- 1 immediate fault output via a dry contact NO/NC.
- 1 supervised auxiliary output of 30 V DC.
- Operates with 2 batteries 12V/2.3Ah.
- Includes test mode.
- Certified according to EN 54-2 and EN 54-4 standards.

More information

Specifications	
Serie	CCG
Installation	2-wire
Technology	Conventional
Number of zones	2
Number of zones (max.)	2
Devices Line (max.)	32
Exit relay.	2
Mermaid output.	2
Signaling	Led,Acoustically
Input voltage (Vac)	230
Use	Indoor
Dimensions - High (mm)	240
Dimensions - Width (mm)	248
Dimensions - Deep (mm)	105
Weight (kg.)	2.2

Accessories

- Series 50 conventional rate-of-rise heat detector
- Conventional indoor optical-acoustic siren
- Conventional resettable manual call point
- Outdoor Siren "FIRE"

Visit in the website: <https://www.golmar.es/products/ccg-02zmini>