

Compact conventional 12-zone control panel



Reference: CCG-12Z
Product code: 21111039
EAN code: 8429898026312



Main characteristics

- Conventional fire detection control panel Series CCG with 12 zones
- Certified according to EN54-2 and EN54-4 standards
- Metal enclosure with ABS plastic front panel
- Allows control of conventional GOLMAR detectors and push buttons (up to 32 total)
- Distinguishes between detector alarm and push button alarm
- 2 supervised outputs for sirens, with a total maximum current of 2A
- 1 alarm output (NO/NC) and 1 fault output (NO) via volt-free relays
- 1 auxiliary output 30 V DC, with a maximum current of 750 mA
- Optical and acoustic indicators by zone
- Requires 2 BAT-7A batteries (not included)
- Dimensions: 331(W) x 363(H) x 96(D) mm

More information

Specifications	
Serie	CCG
Installation	2-wire
Technology	Conventional
Number of zones	12
Number of zones (max.)	12
Devices Line (max.)	32
Battery charger	Yes
Exit relay.	2
Mermaid output.	2
Alarm output	0
Signaling	Led,Acoustically
Input voltage (Vac)	230
Use	Indoor
Dimensions - High (mm)	363
Dimensions - Width (mm)	331
Dimensions - Deep (mm)	96

Accessories

- Conventional resettable manual call point
- Outdoor Siren "FIRE"
- Conventional indoor optical-acoustic siren

Visit in the website: <https://www.golmar.es/products/ccg-12z>