

12-Zone Conventional Control Panel with CRI and APP Connectivity



Reference: CCG-12ZPLUS

Product code: 21111043

EAN code: 8429898034652



Main characteristics

- 12-zone conventional fire alarm panel with **APP (SISCOM)** and **CRA transmission (cards not included)**
- Up to 16 supervised relay outputs (wet contact) or non-supervised outputs (NO/NC) as additional modules not included
- Backlit LCD display with 2 lines and 16 characters
- 3000-event history log with date and time
- 2 supervised siren outputs, S1 and S2, with programmable delay up to 09:59 min
- ALARM and FAULT outputs with dry contact and resettable fuse protection
- 2 auxiliary 30 VDC outputs (resettable 30VR and non-resettable 30V) for external power supply
- Test mode for quick testing of detectors and call points
- Configurable detection thresholds and possibility of using the last zone as an external supervisory input
- Configuration through **GOLMARFIRE** software
- Integrated Spanish and English languages
- IP30 metal enclosure with space for 2 batteries of 12 V / 7 Ah (not included)
- EN54-2/A1 and EN54-4/A1 certified

Accessories

- Series 50 Conventional Thermal Heat Detector
- Conventional Optical Smoke Detector - Series 50
- Conventional resettable manual call point
- Outdoor Siren "FIRE"
- Series 50 conventional rate-of-rise heat detector
- Series 50 conventional optical-heat detector
- Conventional indoor optical-acoustic siren

Visit in the website: <https://www.golmar.es/products/ccg-12zplus>

Golmar Sistemas de Comunicación S.A.

Silici 13 • 08940 Cornellà de Llobregat (Barcelona) • Tel: +34 934 800 696 • golmar@golmar.es • www.golmar.es